

COLOR LASER DISPLAY EMPLOYING EXCITATION SOLID LASER UNIT, FIBER
LASER UNIT, OR SEMICONDUCTOR LASER UNIT

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to a color laser display of a type where a screen is scanned with three-color laser light, and more particularly to a color laser display in which an excitation solid laser unit with a Pr^{3+} -doped solid-state laser crystal, or a fiber laser unit with a fiber having a Pr^{3+} -doped core, or a semiconductor laser unit with a GaN semiconductor laser element for exciting a surface-emitting semiconductor element, is employed as a laser light source.

Description of the Related Art

There is a conventional color laser display in which an image is projected onto a screen, which displays each color when irradiated with red, green, and blue light, by scanning the screen with laser light modulated based on each color image signal. In another conventional color laser display, an image obtained by modulating laser light with a spatial modulation element is projected onto a screen by a projection optics system. These types of color laser displays require a laser light source, whose output is of the order of W (watt), in order to meet the high-brightness requirement. Because of this, a high-output gas laser, such as an Ar^+ gas laser, a Kr^+ gas laser, etc., has been used as the laser light source. However, the gas laser has the

disadvantage that its device size is increased and manufacturing costs are considerably high, because the energy conversion efficiency is low such as about 0.1% and a cooling mechanism is necessary.

5 Hence, excitation second-harmonic-generation (SHG) solid lasers have recently been used as visible short-wavelength laser light sources, as described in Jpn. J. Laser Focus World, p.52 (December 1997). For instance, an yttrium aluminum garnet (YAG) laser unit, which employs an excitation solid laser element of oscillating wavelength 1064 nm to emit laser light of green wavelength 532 nm, is higher in energy conversion efficiency than the aforementioned gas laser.

10 However, noise due to a conflict of longitudinal modes will occur as the aforementioned excitation SHG laser unit generates higher output. For example, Jpn. J. Laser Focus World (p 243, May 1998) discloses that an amount of noise due to the blue and green solid laser elements is 3% or less, while an amount of noise due to the red solid laser element is as much as 50%.

15 To control these longitudinal modes, it is conceivable to insert, for example, an etalon as a wavelength selecting element. However, in such a case, realization of perfect single mode oscillation results in a great loss in efficiency, and consequently, high output is no longer obtainable and there arises a problem that the laser display will not be able to have high
20 brightness. Thus, in the case of employing the excitation SHG solid laser unit as a light source for a laser display, a reduction

in the size is attainable, but numerous problems remain unsolved with respect to high efficiency, device performance, and costs.

SUMMARY OF THE INVENTION

5 The present invention has been made in view of the problems found in the prior art. Accordingly, it is the primary object of the present invention to provide a color laser display that is capable of realizing size reduction, high efficiency, and noise reduction.

To achieve this end and in accordance with an important aspect of the present invention, there is provided a first color laser display comprising:

a red laser light source for emitting red laser light;

a green laser light source for emitting green laser light;

15 a blue laser light source for emitting blue laser light;

modulation means for modulating the red laser light, the green laser light, and the blue laser light, based on a red image signal, a green image signal, and a blue image signal;

20 a screen for displaying red, green, and blue when irradiated with the red laser light, the green laser light, and the blue laser light; and

projection means for projecting the red laser light, the green laser light, and the blue laser light onto the screen so that an image, carrying the red, green, and blue image signals, 25 is displayed on the screen;

wherein an excitation solid laser unit, having a

solid-state laser crystal doped with Pr^{3+} and a GaN semiconductor laser element for exciting the solid-state laser crystal, is employed as at least one of the red laser light source, the green laser light source, or the blue laser light source.

5 In the first color laser display, the excitation solid laser unit may emit laser light of wavelength 600 to 660 nm by a transition of $^3\text{P}_0 \rightarrow ^3\text{F}_2$ or $^3\text{P}_0 \rightarrow ^3\text{H}_6$, and this laser unit can be satisfactorily employed as the red laser light source. The excitation solid laser unit may also emit laser light of wavelength 515 to 555 nm by a transition of $^3\text{P}_1 \rightarrow ^3\text{H}_5$, and this laser unit can be satisfactorily employed as the green laser light source. Furthermore, the excitation solid laser unit may emit laser light of wavelength 465 to 495 nm by a transition of $^3\text{P}_0 \rightarrow ^3\text{H}_4$, and this laser unit can be satisfactorily employed as the blue laser light source.

10
15 In accordance with another important aspect of the present invention, there is provided a second color laser display comprising:

20 a red laser light source for emitting red laser light;
a green laser light source for emitting green laser light;

a blue laser light source for emitting blue laser light;
modulation means for modulating the red laser light, the green laser light, and the blue laser light, based on a red image signal, a green image signal, and a blue image signal;
25 a screen for displaying red, green, and blue when

irradiated with the red laser light, the green laser light, and the blue laser light; and

projection means for projecting the red laser light, the green laser light, and the blue laser light onto the screen
5 so that an image, carrying the red, green, and blue image signals, is displayed on the screen;

wherein a fiber laser unit, having a fiber with a Pr^{3+} -doped core and a GaN semiconductor laser element for exciting the fiber, is employed as at least one of the red laser light source, the green laser light source, or the blue laser light source.
10

As with the first color laser display, the excitation solid laser unit of the second color laser display may emit laser light of wavelength 600 to 660 nm by a transition of $^3\text{P}_0 \rightarrow ^3\text{F}_2$ or $^3\text{P}_0 \rightarrow ^3\text{H}_6$, and this laser unit can be satisfactorily employed as the red laser light source. In addition, the excitation solid laser unit of the second color laser display may emit laser light of wavelength 515 to 555 nm by a transition of $^3\text{P}_1 \rightarrow ^3\text{H}_5$, and this laser unit can be satisfactorily employed as the green laser light source. Furthermore, the excitation solid laser unit of the second color laser display may emit laser light of wavelength 465 to 495 nm by a transition of $^3\text{P}_0 \rightarrow ^3\text{H}_4$, and this laser unit can be satisfactorily employed as the blue laser light source.
15
20

In accordance with still another important aspect of the present invention, there is provided a third color laser display comprising:
25

a red laser light source for emitting red laser light;
a green laser light source for emitting green laser
light;

a blue laser light source for emitting blue laser light;
5 modulation means for modulating the red laser light,
the green laser light, and the blue laser light, based on a red
image signal, a green image signal, and a blue image signal;

a screen for displaying red, green, and blue when
irradiated with the red laser light, the green laser light, and
the blue laser light; and

projection means for projecting the red laser light,
the green laser light, and the blue laser light onto the screen
so that an image, carrying the red, green, and blue image signals,
is displayed on the screen;

10 wherein a semiconductor laser unit is employed as at
least one of the red laser light source, the green laser light
source, or the blue laser light source, and the semiconductor
laser unit includes an excitation light source constructed of
a semiconductor laser element employing a GaN semiconductor in
15 its active layer, and also includes a surface-emitting
semiconductor element for emitting laser light when excited with
the excitation light source.

In a preferred form of the third color laser display,
the surface-emitting semiconductor element of the semiconductor
25 laser unit has an active layer composed of InGaAlP or InGaP,
the semiconductor laser unit being employed as the red laser

light source. The surface-emitting semiconductor element of the semiconductor laser unit may have an active layer composed of InGaN. In this case, the semiconductor laser unit is employed as the green laser light source and/or the blue laser light source.

Moreover, it is preferable that the surface-emitting semiconductor element of the semiconductor laser unit have an active layer composed of GaN, GaNAs, or InGaNAs.

Furthermore, it is desirable that the semiconductor laser element (for the excitation light source) of the semiconductor laser unit of the third color laser display have an active layer composed of InGaN, GaNAs, or InGaNAs. It is also desirable that the semiconductor laser element of the semiconductor laser unit have a stripe width of 5 μm or more.

In the color laser display of the present invention, an excitation solid laser unit with a Pr^{3+} -doped solid-state laser crystal, or a fiber laser unit with a fiber having a Pr^{3+} -doped core, or a semiconductor laser unit with a GaN semiconductor laser element for exciting a surface-emitting semiconductor element, is employed as a red laser light source, a green laser light source, or a blue laser light source. The red laser light, the green laser light, and the blue laser light, emitted from the light sources, are modulated based on red, green, and blue image signals and are projected onto the screen. Therefore, an image carrying these image signals can be displayed on the screen. With this construction, the color laser display of the present invention has the following advantages:

(1) The excitation solid laser unit, the fiber laser unit, and the semiconductor laser unit, employed as the red, green, or blue laser light source, do not require a cooling mechanism as does the conventional gas laser unit. Thus, the color laser display of the present invention is capable of sufficiently reducing the size, compared with the aforementioned conventional color laser displays. In addition, the reduction in the number of components results in a reduced cost. Even in comparison with the case of employing the aforementioned excitation SHG solid laser as a light source, the effect of the reduced cost by the reduction in the number of components is obtained because there is no need to employ a longitudinal mode control element, such as an optical wavelength conversion element, an etalon, etc.

(2) The light-to-light efficiency of the aforementioned excitation SHG solid laser unit is typically about 10 to 20%, whereas those of the excitation solid laser unit, fiber laser unit, and semiconductor laser unit of the present invention typically reach about 30 to 50%. Thus, the present invention is also capable of realizing high efficiency, compared with the conventional color laser display that employs the excitation SHG solid laser unit as the light source.

(3) The aforementioned excitation solid laser unit, fiber laser unit, and semiconductor laser unit of the present invention do not employ an optical wavelength conversion element in order to obtain a desired wavelength as does the excitation

SHG solid laser unit. As a result, there is no occurrence of noise due to a conflict of longitudinal modes that results from wavelength conversion. Thus, the color laser display of the present invention is capable of suppressing an amount of noise to about less than 1%, for example.

(4) The GaN semiconductor laser element for excitation, employed in the color laser display of the present invention, is able to generate high output because its COD value (i.e., the maximum light output at the time of end-face destruction) is very high compared with other GaAs semiconductor laser elements, etc. This enables the color laser display of the present invention to display a high-brightness image.

(5) Particularly, the fiber laser unit employed in the second color laser display of the present invention is able to generate considerably high output as it does not have the problem of a thermal lens, etc. Thus, the second color laser display is capable of displaying a higher-brightness image.

(6) The color laser display of the present invention has the advantage that it can obtain modulated light by directly modulating the excitation GaN semiconductor laser element.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be described in further detail with reference to the accompanying drawings wherein:

FIG. 1 is a diagrammatic perspective view showing a color laser display constructed according to a first embodiment of the present invention;

FIG. 2 is a diagrammatic side view of the fiber laser unit employed in the color laser display of FIG. 1;

FIG. 3 is a cross sectional view of the fiber employed in the fiber laser unit shown in FIG. 2;

5 FIG. 4 is a diagrammatic side view of another fiber laser unit employed in the color laser display of FIG. 1;

FIG. 5 is a diagrammatic side view showing the construction of a first semiconductor laser unit employed in a color laser display of a second embodiment of the present invention;

FIG. 6 is a diagrammatic sectional view of a semiconductor laser element constituting the semiconductor laser unit of FIG. 5;

FIG. 7 is a diagrammatic sectional view of a surface-emitting semiconductor laser element constituting the semiconductor laser unit of FIG. 5;

FIG. 8A is a diagrammatic side view showing the construction of a second or third semiconductor laser unit employed in the color laser display of the second embodiment of the present invention;

FIG. 8B is a diagrammatic side view showing an alternation of the semiconductor laser unit shown in FIG. 8A;

FIG. 9 is a diagrammatic sectional view of a surface-emitting semiconductor laser element constituting the semiconductor laser unit of FIG. 8; and

FIG. 10 is a diagrammatic side view showing an

excitation solid laser unit employed in the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring more particularly to the drawings which are for the purpose of illustrating preferred embodiments of the present invention only, and not for the purpose of limiting same, Fig. 1 illustrates a color laser display that is a first embodiment of the present invention.

As illustrated in Fig. 1, the color laser display has a red laser light source 1a for emitting red laser light 10R, a green laser light source 1b for emitting green laser light 10G, a blue laser light source 1b for emitting blue laser light 10B, a first optical modulator 2a for modulating the red laser light 10R on the basis of a red image signal, a second optical modulator 2b for modulating the green laser light 10G on the basis of a green image signal, and a third optical modulator 2c for modulating the blue laser light 10B on the basis of a blue image signal.

The modulated red laser light 10R is reflected at a first mirror 3a and transmitted through a second dichroic mirror 3b and a third dichroic mirror 3c. The modulated green laser light 10G is reflected at the second dichroic mirror 3b and transmitted through the third dichroic mirror 3c. The modulated blue laser light 10B is reflected at the third dichroic mirror 3c. In this manner, the modulated red laser light 10R, the modulated green laser light 10G, and the modulated blue laser light 10B are coupled into a single beam of light.

The red laser light 10R, the green laser light 10G, and the blue laser light 10B are transmitted through an electro-optic deflector 4, in which a correction of raster pitch unevenness is made. Then, the red laser light 10R, the green laser light 10G, and the blue laser light 10B are wobbled by a first wobbling galvanometer 5 and are reflected and deflected for vertical scanning by a second galvanometer 6. Next, the red laser light 10R, the green laser light 10G, and the blue laser light 10B are collected by a relay lens 7 and are reflected and deflected for horizontal scanning by a rotating polygon mirror 8.

The red laser light 10R, the green laser light 10G, and the blue laser light 10B, reflected and deflected for vertical scanning and horizontal scanning by the second galvanometer 6 and the rotating polygon mirror 8, are scanned in two dimensions on a screen 9. This screen 9 is formed, for example, from an appropriate substrate coated on the surface with white paint, a diffusing material, etc. The screen 9 diffuses and reflects red light, green light, and blue light, respectively, when irradiated with the red laser light 10R, the green laser light 10G, and the blue laser light 10B.

The red laser light 10R, the green laser light 10G, and the blue laser light 10B having been modulated on the basis of red, green, and blue image signals are scanned two-dimensionally on the screen 9, whereby an image signal carrying the three color signals is projected onto this screen

9. Note that the screen 9 may be of a transmission type.

While the first embodiment has adopted the method of projecting an image onto the screen by scanning the screen two-dimensionally with each color laser light, the present invention may adopt a method in which each color laser light is modulated with a spatial modulation element (e.g., a liquid crystal panel, a digital micromirror device (DMD), grating light valve (GLV), etc.) and an image obtained by the modulation is projected onto a screen.

Now, the red laser light source 1a, the green laser light source 1b, and the blue laser light source 1c will be described in detail. In the first embodiment, fiber laser units are employed as these light sources and constructed so that a fiber with a Pr^{3+} -doped core is excited with GaN semiconductor laser elements.

Fig. 2 illustrates a fiber laser unit used as the red laser light source 1a of the laser light sources 1a, 1b, and 1c. This fiber laser unit comprises two semiconductor laser elements 111 for emitting laser light (excitation light) 110, two collimator lenses 112 for forming the emitted laser light 110 into a collimated beam of laser light, a polarization beam splitter 113 for polarizing and coupling two beams of laser light 110, a collective lens 114 for collecting a single beam of laser light 110 obtained by the polarization beam splitter 113, and a fiber 115 with a Pr^{3+} -doped core.

The semiconductor laser element 111 employs a broad

area type high-output InGaN semiconductor laser having an oscillating wavelength of 440 nm. The output of each of the semiconductor laser elements 111 in the first embodiment is 2 W and the output of the coupled laser light 110 is thus 4 W.

5 As illustrated in the cross sectional configuration of Fig. 3, the fiber 115 is made up of a circular cross-section core 120, a first rectangular cross-section clad 121 disposed outside the core 120, and a second circular cross-section clad 122 disposed outside the first clad 121. The core 120 is composed of Zr fluoride glass doped, for example, 2% with Pr^{3+} (e.g., $\text{ZrF}_4\text{-BaF}_2\text{-LaF}_3\text{-AlF}_3\text{-NaF-PbF}_2$ (ZBLANP)). The first clad 121 is composed of $\text{ZrF}_4\text{-BaF}_2\text{-LaF}_3\text{-AlF}_3\text{-NaF}$ (ZBLAN) by way of example, and the second clad 122 is composed of a polymer by way of example.

Note that the core 120 is not limited to the
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995
1000
1005
1010
1015
1020
1025
1030
1035
1040
1045
1050
1055
1060
1065
1070
1075
1080
1085
1090
1095
1100
1105
1110
1115
1120
1125
1130
1135
1140
1145
1150
1155
1160
1165
1170
1175
1180
1185
1190
1195
1200
1205
1210
1215
1220
1225
1230
1235
1240
1245
1250
1255
1260
1265
1270
1275
1280
1285
1290
1295
1300
1305
1310
1315
1320
1325
1330
1335
1340
1345
1350
1355
1360
1365
1370
1375
1380
1385
1390
1395
1400
1405
1410
1415
1420
1425
1430
1435
1440
1445
1450
1455
1460
1465
1470
1475
1480
1485
1490
1495
1500
1505
1510
1515
1520
1525
1530
1535
1540
1545
1550
1555
1560
1565
1570
1575
1580
1585
1590
1595
1600
1605
1610
1615
1620
1625
1630
1635
1640
1645
1650
1655
1660
1665
1670
1675
1680
1685
1690
1695
1700
1705
1710
1715
1720
1725
1730
1735
1740
1745
1750
1755
1760
1765
1770
1775
1780
1785
1790
1795
1800
1805
1810
1815
1820
1825
1830
1835
1840
1845
1850
1855
1860
1865
1870
1875
1880
1885
1890
1895
1900
1905
1910
1915
1920
1925
1930
1935
1940
1945
1950
1955
1960
1965
1970
1975
1980
1985
1990
1995
2000
2005
2010
2015
2020
2025
2030
2035
2040
2045
2050
2055
2060
2065
2070
2075
2080
2085
2090
2095
2100
2105
2110
2115
2120
2125
2130
2135
2140
2145
2150
2155
2160
2165
2170
2175
2180
2185
2190
2195
2200
2205
2210
2215
2220
2225
2230
2235
2240
2245
2250
2255
2260
2265
2270
2275
2280
2285
2290
2295
2300
2305
2310
2315
2320
2325
2330
2335
2340
2345
2350
2355
2360
2365
2370
2375
2380
2385
2390
2395
2400
2405
2410
2415
2420
2425
2430
2435
2440
2445
2450
2455
2460
2465
2470
2475
2480
2485
2490
2495
2500
2505
2510
2515
2520
2525
2530
2535
2540
2545
2550
2555
2560
2565
2570
2575
2580
2585
2590
2595
2600
2605
2610
2615
2620
2625
2630
2635
2640
2645
2650
2655
2660
2665
2670
2675
2680
2685
2690
2695
2700
2705
2710
2715
2720
2725
2730
2735
2740
2745
2750
2755
2760
2765
2770
2775
2780
2785
2790
2795
2800
2805
2810
2815
2820
2825
2830
2835
2840
2845
2850
2855
2860
2865
2870
2875
2880
2885
2890
2895
2900
2905
2910
2915
2920
2925
2930
2935
2940
2945
2950
2955
2960
2965
2970
2975
2980
2985
2990
2995
3000
3005
3010
3015
3020
3025
3030
3035
3040
3045
3050
3055
3060
3065
3070
3075
3080
3085
3090
3095
3100
3105
3110
3115
3120
3125
3130
3135
3140
3145
3150
3155
3160
3165
3170
3175
3180
3185
3190
3195
3200
3205
3210
3215
3220
3225
3230
3235
3240
3245
3250
3255
3260
3265
3270
3275
3280
3285
3290
3295
3300
3305
3310
3315
3320
3325
3330
3335
3340
3345
3350
3355
3360
3365
3370
3375
3380
3385
3390
3395
3400
3405
3410
3415
3420
3425
3430
3435
3440
3445
3450
3455
3460
3465
3470
3475
3480
3485
3490
3495
3500
3505
3510
3515
3520
3525
3530
3535
3540
3545
3550
3555
3560
3565
3570
3575
3580
3585
3590
3595
3600
3605
3610
3615
3620
3625
3630
3635
3640
3645
3650
3655
3660
3665
3670
3675
3680
3685
3690
3695
3700
3705
3710
3715
3720
3725
3730
3735
3740
3745
3750
3755
3760
3765
3770
3775
3780
3785
3790
3795
3800
3805
3810
3815
3820
3825
3830
3835
3840
3845
3850
3855
3860
3865
3870
3875
3880
3885
3890
3895
3900
3905
3910
3915
3920
3925
3930
3935
3940
3945
3950
3955
3960
3965
3970
3975
3980
3985
3990
3995
4000
4005
4010
4015
4020
4025
4030
4035
4040
4045
4050
4055
4060
4065
4070
4075
4080
4085
4090
4095
4100
4105
4110
4115
4120
4125
4130
4135
4140
4145
4150
4155
4160
4165
4170
4175
4180
4185
4190
4195
4200
4205
4210
4215
4220
4225
4230
4235
4240
4245
4250
4255
4260
4265
4270
4275
4280
4285
4290
4295
4300
4305
4310
4315
4320
4325
4330
4335
4340
4345
4350
4355
4360
4365
4370
4375
4380
4385
4390
4395
4400
4405
4410
4415
4420
4425
4430
4435
4440
4445
4450
4455
4460
4465
4470
4475
4480
4485
4490
4495
4500
4505
4510
4515
4520
4525
4530
4535
4540
4545
4550
4555
4560
4565
4570
4575
4580
4585
4590
4595
4600
4605
4610
4615
4620
4625
4630
4635
4640
4645
4650
4655
4660
4665
4670
4675
4680
4685
4690
4695
4700
4705
4710
4715
4720
4725
4730
4735
4740
4745
4750
4755
4760
4765
4770
4775
4780
4785
4790
4795
4800
4805
4810
4815
4820
4825
4830
4835
4840
4845
4850
4855
4860
4865
4870
4875
4880
4885
4890
4895
4900
4905
4910
4915
4920
4925
4930
4935
4940
4945
4950
4955
4960
4965
4970
4975
4980
4985
4990
4995
5000
5005
5010
5015
5020
5025
5030
5035
5040
5045
5050
5055
5060
5065
5070
5075
5080
5085
5090
5095
5100
5105
5110
5115
5120
5125
5130
5135
5140
5145
5150
5155
5160
5165
5170
5175
5180
5185
5190
5195
5200
5205
5210
5215
5220
5225
5230
5235
5240
5245
5250
5255
5260
5265
5270
5275
5280
5285
5290
5295
5300
5305
5310
5315
5320
5325
5330
5335
5340
5345
5350
5355
5360
5365
5370
5375
5380
5385
5390
5395
5400
5405
5410
5415
5420
5425
5430
5435
5440
5445
5450
5455
5460
5465
5470
5475
5480
5485
5490
5495
5500
5505
5510
5515
5520
5525
5530
5535
5540
5545
5550
5555
5560
5565
5570
5575
5580
5585
5590
5595
5600
5605
5610
5615
5620
5625
5630
5635
5640
5645
5650
5655
5660
5665
5670
5675
5680
5685
5690
5695
5700
5705
5710
5715
5720
5725
5730
5735
5740
5745
5750
5755
5760
5765
5770
5775
5780
5785
5790
5795
5800
5805
5810
5815
5820
5825
5830
5835
5840
5845
5850
5855
5860
5865
5870
5875
5880
5885
5890
5895
5900
5905
5910
5915
5920
5925
5930
5935
5940
5945
5950
5955
5960
5965
5970
5975
5980
5985
5990
5995
6000
6005
6010
6015
6020
6025
6030
6035
6040
6045
6050
6055
6060
6065
6070
6075
6080
6085
6090
6095
6100
6105
6110
6115
6120
6125
6130
6135
6140
6145
6150
6155
6160
6165
6170
6175
6180
6185
6190
6195
6200
6205
6210
6215
6220
6225
6230
6235
6240
6245
6250
6255
6260
6265
6270
6275
6280
6285
6290
6295
6300
6305
6310
6315
6320
6325
6330
6335
6340
6345
6350
6355
6360
6365
6370
6375
6380
6385
6390
6395
6400
6405
6410
6415
6420
6425
6430
6435
6440
6445
6450
6455
6460
6465
6470
6475
6480
6485
6490
6495
6500
6505
6510
6515
6520
6525
6530
6535
6540
6545
6550
6555
6560
6565
6570
6575
6580
6585
6590
6595
6600
6605
6610
6615
6620
6625
6630
6635
6640
6645
6650
6655
6660
6665
6670
6675
6680
6685
6690
6695
6700
6705
6710
6715
6720
6725
6730
6735
6740
6745
6750
6755
6760
6765
6770
6775
6780
6785
6790
6795
6800
6805
6810
6815
6820
6825
6830
6835
6840
6845
6850
6855
6860
6865
6870
6875
6880
6885
6890
6895
6900
6905
6910
6915
6920
6925
6930
6935
6940
6945
6950
6955
6960
6965
6970
6975
6980
6985
6990
6995
7000
7005
7010
7015
7020
7025
7030
7035
7040
7045
7050
7055
7060
7065
7070
7075
7080
7085
7090
7095
7100
7105
7110
7115
7120
7125
7130
7135
7140
7145
7150
7155
7160
7165
7170
7175
7180
7185
7190
7195
7200
7205
7210
7215
7220
7225
7230
7235
7240
7245
7250
7255
7260
7265
7270
7275
7280
7285
7290
7295
7300
7305
7310
7315
7320
7325
7330
7335
7340
7345
7350
7355
7360
7365
7370
7375
7380
7385
7390
7395
7400
7405
7410
7415
7420
7425
7430
7435
7440
7445
7450
7455
7460
7465
7470
7475
7480
7485
7490
7495
7500
7505
7510
7515
7520
7525
7530
7535
7540
7545
7550
7555
7560
7565
7570
7575
7580
7585
7590
7595
7600
7605
7610
7615
7620
7625
7630
7635
7640
7645
7650
7655
7660
7665
7670
7675
7680
7685
7690
7695
7700
7705
7710
7715
7720
7725
7730
7735
7740
7745
7750
7755
7760
7765
7770
7775
7780
7785
7790
7795
7800
7805
7810
7815
7820
7825
7830
7835
7840
7845
7850
7855
7860
7865
7870
7875
7880
7885
7890
7895
7900
7905
7910
7915
7920
7925
7930
7935
7940
7945
7950
7955
7960
7965
7970
7975
7980
7985
7990
7995
8000
8005
8010
8015
8020
8025
8030
8035
8040
8045
8050
8055
8060
8065
8070
8075
8080
8085
8090
8095
8100
8105
8110
8115
8120
8125
8130
8135
8140
8145
8150
8155
8160
8165
8170
8175
8180
8185
8190
8195
8200
8205
8210
8215
8220
8225
8230
8235
8240
8245
8250
8255
8260
8265
8270
8275
8280
8285
8290
8295
8300
8305
8310
8315
8320
8325
8330
8335
8340
8345
8350
8355
8360
8365
8370
8375
8380
8385
8390
8395
8400
8405
8410
8415
8420
8425
8430
8435
8440
8445
8450
8455
8460
8465
8470
8475
8480
8485
8490
8495
8500
8505
8510
8515
8520
8525
8530
8535
8540
8545
8550
8555
8560
8565
8570
8575
8580
8585
8590
8595
8600
8605
8610
8615
8620
8625
8630
8635
8640
8645
8650
8655
8660
8665
8670
8675
8680
8685
8690
8695
8700
8705
8710
8715
8720
8725
8730
8735
8740
8745
8750
8755
8760
8765
8770
8775
8780
8785
8790
8795
8800
8805
8810
8815
8820
8825
8830
8835
8840
8845
8850
8855
8860
8865
8870
8875
8880
8885
8890
8895
8900
8905
8910
8915
8920
8925
8930
8935
8940
8945
8950
8955
8960
8965
8970
8975
8980
8985
8990
8995
9000
9005
9010
9015
9020
9025
9030
9035
9040
9045
9050
9055
9060
9065
9070
9075
9080
9085
9090
9095
9100
9105
9110
9115
9120
9125
9130
9135
9140
9145
9150
9155
9160
9165
9170
9175
9180
9185
9190
9195
9200
9205
9210
9215
9220
9225
9230
9235
9240
9245
9250
9255
9260
9265
9270
9275
9280
9285
9290
9295
9300
9305
9310
9315
9320
9325
9330
9335
9340
9345
9350
9355
9360
9365
9370
9375
9380
9385
9390
9395
9400
9405
9410
9415
9420
9425
9430
9435
9440
9445
9450
9455
9460
9465
9470
9475
9480
9485
9490
9495
9500
9505
9510
9515
9520
9525
9530
9535
9540
9545
9550
9555
9560
9565
9570
9575
9580
9585
9590
9595
9600
9605
9610
9615
9620
9625
9630
9635
9640
9645
9650
9655
9660
9665
9670
9675
9680
9685
9690
9695
9700
9705
9710
9715
9720
9725
9730
9735
9740
9745
9750
9755
9760
9765
9770
9775
9780
9785
9790
9795
9800
9805
9810
9815
9820
9825
9830
9835
9840
9845
9850
9855
9860
9865
9870
9875
9880
9885
9890
9895
9900
9905
9910
9915
9920
9925
9930
9935
9940
9945
9950
9955
9960
9965
9970
9975
9980
9985
9990
9995
10000
10005
10010
10015
10020
10025
10030
10035
10040
10045
10050
10055
10060
10065
10070
10075
10080
10085
10090
10095
10100
10105
10110
10115
10120
10125
10130
10135
10140
101

nm to occur. This fluorescence also propagates in a waveguide mode along the core 120.

In the ZBLANP core 120, in addition to the transition of $^3P_0 \rightarrow ^3F_3$, a transition of $^3P_1 \rightarrow ^3H_5$ causes fluorescence of wavelength 605 nm to occur, a transition of $^3P_0 \rightarrow ^3F_2$ causes fluorescence of wavelength 605 nm to occur, and a transition of $^3P_0 \rightarrow ^3H_4$ causes fluorescence of wavelength 491 nm to occur.

Hence, the fiber 115 is provided at the light incidence end face 115a thereof with a special coating which becomes highly reflective with respect to fluorescence of wavelength 650 nm and becomes reflectionless with respect to fluorescence of wavelengths 520 nm, 605 nm, and 491 nm and excitation light of wavelength 440 nm and is provided at the light emergence end face 115b with a coating which allows only 1% transmission of fluorescence of wavelength 650 nm.

With these coatings, the aforementioned fluorescence of wavelength 650 nm resonates between both end faces 115a and 115b of the fiber 115 and causes laser oscillation. In this manner, the red laser light 10R with a wavelength of 650 nm occurs and emerges forward from the light emergence end face 115b.

Note that the first embodiment is constructed such that the red laser light 10R propagates in a single mode along the core 120, while the laser light (excitation light) 110 propagates in a multi mode. This construction renders it possible to use the broad area type high-output semiconductor laser element 111 as an excitation light source and input the laser light 110 to

the fiber 115 with a high coupling efficiency.

Besides, there is an enhanced possibility that the laser light 110 will propagate along irregular reflection paths within the cross section of the first clad 121 and will be incident on the core 120, because the clad cross section is approximately rectangular.

In this way, high oscillation efficiency is assured and the red laser light 10R with high output is obtained. The output of the red laser light 10R in the first embodiment is 2 W.

Next, a description will be given of the green laser light source 1b. This green laser light source 1b has the same construction as the red laser light source 1a, except that the coatings on both end faces of a fiber differ from those on both end faces of the fiber 115 of the red laser light source 1a in order to transmit the green laser light 10G of wavelength 520 nm. As with the red laser light source 1a, two broad area type high-output InGaN semiconductor lasers with an oscillating wavelength of 440 nm and an output of 2 W are employed as excitation light sources. Therefore, the output of the coupled laser light is 4 W. The output of the green laser light 10G at this time is 1 W.

Next, a description will be made of the blue laser light source 1c. This blue laser light source 1c also has the same construction as the red laser light source 1a, except that the coatings on both end faces of a fiber differ from those on both

end faces of the fiber 115 of the red laser light source 1a in order to transmit the blue laser light 10B of wavelength 491 nm. However, the excitation light source in this case employs a combination of two polarization coupling units having an output of 4 W, since blue laser light is low in oscillation efficiency. As with the aforementioned case, each coupling unit includes two broad area type high-output InGaN semiconductors having an oscillating wavelength of 440 nm and an output of 2 W. In this manner, excitation light with an output of 8 W is obtained.

Fig. 4 illustrates the construction of the two polarization coupling units combined together. As illustrated in the figure, the two polarization coupling units 130 are coupled with the Y-shaped branch portions of a fiber 131. The laser light 110 emerging from the fiber 131 is collimated by a collimator lens 132. Next, the collimated laser light 110 is collected by a collective lens 133 and input to a fiber 115.

Note that in the case where the fiber laser units are employed as in the first embodiment, the red laser light 10R, the green laser light 10G, and the blue laser light 10B, emitted from the fiber laser units, are in a longitudinal multi mode. Therefore, the wobbling galvanometer 5 shown in Fig. 1 may be omitted according to circumstances. In addition, a surface-tilt correction optics system employing cylindrical lenses may be employed instead of the electro-optic deflector 4 which performs a correction of pitch unevenness. Furthermore, the optical modulators 2a, 2b, and 2c can be replaced, for example, with

acousto-optic modulators (AOMs) or electro-optic modulators (EOMs).

Now, a color laser display according to a second embodiment of the present invention will be described in detail. The color laser display of the second embodiment is differentiated from that of the first embodiment in that instead of the fiber laser units (i.e., the laser light sources 1a, 1b, and 1c), semiconductor laser units with surface-emitting semiconductor elements which are excited by semiconductor laser elements are employed as red, green, and blue light sources.

Of the three semiconductor lasers, the first semiconductor laser unit as the red laser light source will be described with reference to Figs. 5, 6, and 7. Fig. 5 shows the construction of the first semiconductor laser unit. Figs. 6 and 7 show the semiconductor laser element 74 and surface-emitting semiconductor element 39 of the first semiconductor laser unit, respectively.

Initially, the method of fabricating the semiconductor laser element 74 for excitation will be described with reference to Fig. 6. An $n\text{-Ga}_{1-x_1}\text{Al}_{x_1}\text{N}/\text{GaN}$ superlattice cladding layer 62 ($0 < x_1 < 1$), an n - or i -GaN waveguide layer 63, an $\text{In}_{1-x_2}\text{Ga}_{x_2}\text{N}$ (doped with Si)/ $\text{In}_{1-x_3}\text{Ga}_{x_3}\text{N}$ multiple-quantum-well active layer 64 ($0 < x_2 < x_3 < 0.5$), a $p\text{-Ga}_{1-x_5}\text{Al}_{x_5}\text{N}$ carrier blocking layer 65 ($0 < x_5 < 0.5$), an n - or i -GaN waveguide layer 66, a $p\text{-Ga}_{1-x_1}\text{Al}_{x_1}\text{N}/\text{GaN}$ superlattice cladding layer 67 ($0 < x_1 < 1$), and a p -GaN contact layer 68, are formed on an n -GaN (0001)

substrate 61 by organometallic vapor phase epitaxy. Then, a SiO_2 insulating film 69 is formed on the p-GaN contact layer 68, and a striped area of the insulating film 69 having a width of about $100\ \mu\text{m}$ is removed by normal lithography so that the p-GaN contact layer 68 is exposed. Next, a p-side electrode 70 is formed on the insulating film 69 and the exposed portion of the p-GaN contact layer 68. Thereafter, the substrate 61 is polished and an n-side electrode 71 is formed on the polished surface of the substrate 61. A laser resonator is formed by cleavage and provided with a high reflective coating and a low reflective coating. The coated structure is cleaved parallel to the paper surface, whereby the semiconductor laser element 74 is fabricated. The oscillating wavelength of this broad area type InGaN semiconductor laser element 74 is 410 nm and the output is 2 W.

Next, the method of fabricating the surface-emitting semiconductor element 39 will be described with reference to Fig. 7. Notice that λ to be described later is the wavelength of light which the surface-emitting semiconductor element 39 emits when excited with excitation light and that n_{InAlP} , n_{InGaAlP} , n_{SiO_2} , and n_{ZrO_2} are refractive indices for InAlP, InGaAlP, SiO_2 , and ZrO_2 at the wavelength λ , respectively.

Initially, an $\text{In}_{0.5}(\text{Ga}_{1-x_5}\text{Al}_{x_5})_{0.5}\text{P}$ cladding layer 32, an $\text{In}_{0.5}(\text{Ga}_{1-x_2}\text{Al}_{x_2})_{0.5}\text{P}$ lower confining layer 33, an $\text{In}_{0.5}(\text{Ga}_{1-x_3}\text{Al}_{x_3})_{0.5}\text{P}/\text{In}_{0.5}(\text{Ga}_{1-x_4}\text{Al}_{x_4})_{0.5}\text{P}$ multiple-quantum-well active layer 34, an $\text{In}_{0.5}(\text{Ga}_{1-x_2}\text{Al}_{x_2})_{0.5}\text{P}$ upper confining layer 35,

and an $\text{In}_{0.5}\text{Al}_{0.5}\text{P}/\text{In}_{0.5}(\text{Ga}_{1-x_1}\text{Al}_{x_1})_{0.5}\text{P}$ distributed reflection film 36, are formed on a GaAs substrate 31. It is desirable that the aforementioned composition meet $0 \leq x_4 < x_3 \leq 1$, $x_4 < x_2 < x_5 \leq 1$, $0 \leq x_3 < x_1 \leq x_2$, and $x_3 < x_5 < 1$. Also, the distributed reflection film 36 is comprised of two pairs of $\text{In}_{0.5}\text{Al}_{0.5}\text{P}$ and $\text{In}_{0.5}(\text{Ga}_{1-x_1}\text{Al}_{x_1})_{0.5}\text{P}$ layers. The $\text{In}_{0.5}\text{Al}_{0.5}\text{P}$ layer in each pair has a thickness of $\lambda/4n_{\text{InAlP}}$, and the $\text{In}_{0.5}(\text{Ga}_{1-x_1}\text{Al}_{x_1})_{0.5}\text{P}$ layer in each pair has a thickness of $\lambda/4n_{\text{InGaAlP}}$. Furthermore, the distributed reflection film 36 can be omitted.

Thereafter, a $\text{SiO}_2/\text{ZrO}_2$ distributed reflection film 37 is formed on the $\text{In}_{0.5}\text{Al}_{0.5}\text{P}/\text{In}_{0.5}(\text{Ga}_{1-x_1}\text{Al}_{x_1})_{0.5}\text{P}$ distributed reflection film 36 by electron beam evaporation, etc. The $\text{SiO}_2/\text{ZrO}_2$ distributed reflection film 37 is comprised of 12 pairs of SiO_2 and ZrO_2 layers. The SiO_2 layer in each pair has a thickness of $\lambda/4n_{\text{SiO}_2}$, and the ZrO_2 layer in each pair has a thickness of $\lambda/4n_{\text{ZrO}_2}$. Next, the GaAs substrate 31 is polished with a H_2SO_4 -system etchant, whereby a light-emitting portion of the GaAs substrate 31 is removed. The etching automatically stops when the $\text{In}_{0.5}(\text{Ga}_{1-x_5}\text{Al}_{x_5})_{0.5}\text{P}$ cladding layer 32 is exposed. Next, a ZrO_2 antireflection coating 38 with a thickness of $\lambda/4n_{\text{ZrO}_2}$ is provided on the GaAs substrate 31. Finally, the structure layered as above is cleaved parallel to the paper surface, whereby the surface-emitting semiconductor element 39 is fabricated.

The wavelength λ of light emitted by the aforementioned surface-emitting semiconductor element 39 can be controlled in a range between 600 and 700 nm by the

$\text{In}_{0.5}(\text{Ga}_{1-x}\text{Al}_x)_{0.5}\text{P}$ multiple-quantum-well active layer, and in the second embodiment, the wavelength λ is 650 nm.

Fig. 5 shows the first semiconductor laser unit (for the red laser light source 10R) of the second embodiment of the present invention which employs the aforementioned surface-emitting semiconductor element 39 and InGaN semiconductor laser element 74. This semiconductor laser unit includes an excitation light source 74'; the aforementioned surface-emitting semiconductor element 39 with the aforementioned distributed reflection film 37 bonded to a heat sink 43; a concave mirror 46 which is an output mirror; an external laser resonator 49 constructed of the concave surface of the concave mirror 46 and the distributed reflection film 37 of the surface-emitting semiconductor element 39; and a Brewster plate 45, disposed within the external laser resonator 49, for controlling polarization. The excitation light source 74' is equipped with two broad area type InGaN semiconductor laser elements 74 having an output of 2 W, and polarization coupling means, such as that shown in Fig. 2, for coupling the excitation laser light beams emitted from the two semiconductor laser elements 74. The output of the excitation light source 74' is thus 4 W.

The excitation light 47 of wavelength 410 nm emitted from the excitation light source 74' is collected into the semiconductor layers of the surface-emitting semiconductor element 39 by a lens 42 and excites the surface-emitting

semiconductor element 39. The light emitted from the excited surface-emitting semiconductor element 39 resonates in the external laser resonator 49, and red laser light 48 of wavelength 650 nm emerges from the output mirror 46. The output of the red laser light 48 is 2 W, and as in the first embodiment, it is utilized for scanning the screen 9 two-dimensionally (refer to Fig. 1).

Note that since the GaAs substrate 31 of the surface-emitting semiconductor element 39 is not transparent to the excitation light 47 of wavelength 410 nm, the surface-emitting semiconductor element 39 is excited at the side face thereof, as illustrated in Fig. 5. The second embodiment modulates the semiconductor laser elements 74 of the excitation light source 74' directly, thereby eliminating the external optical modulator 2a employed in the first embodiment. This results in cost reduction.

Next, the second and third semiconductor laser units, which are employed as the green and blue laser light sources, will be described with reference to Figs. 8 and 9. Figs. 8A and 8B show the second or third semiconductor laser unit and an alternation of the semiconductor laser unit, respectively. Fig. 9 shows the cross section of a surface-emitting semiconductor element 89 employed in each of the second and third semiconductor laser units. The excitation light sources 74' of the second and third semiconductor laser units for exciting the surface-emitting semiconductor element 89 are the same as that employed as the

red laser light source 1a of the first semiconductor laser unit. Therefore, they will not be described any further.

Next, the method of fabricating the surface-emitting semiconductor element 89 will be described with reference to Fig. 9. Note that λ to be described later indicates the wavelength of light which the surface-emitting semiconductor element 89 emits when excited with excitation light and that n_{AlN} , n_{GaN} , n_{SiO_2} , and n_{ZrO_2} indicate the refractive indexes of AlN, GaN, SiO₂, and ZrO₂ at the wavelength λ , respectively.

As illustrated in Fig. 9, an $\text{Al}_{z_4}\text{Ga}_{1-z_4}\text{N}$ layer 82 ($0 < z_4 < 0.5$), a GaN confining layer 83, an $\text{In}_{1-z_2}\text{Ga}_{z_2}\text{N}/\text{In}_{1-z_3}\text{Ga}_{z_3}\text{N}$ multiple-quantum-well active layer 84 ($0 < z_2 < z_3 < 0.5$), a GaN confining layer 85, and a reflection film 86 consisting of two pairs of AlN (with a thickness of $\lambda/4n_{\text{AlN}}$) and GaN (with a thickness of $\lambda/4n_{\text{GaN}}$) layers, are formed on a GaN (0001) substrate 81 by organometallic vapor phase epitaxy. Then, a SiO₂ (with a thickness of $\lambda/4n_{\text{SiO}_2}$)/ZrO₂ (with a thickness of $\lambda/4n_{\text{ZrO}_2}$) distributed reflection film 87 is formed on the reflection film 86 by electron beam evaporation, etc. Next, the GaN substrate 81 is polished and provided with a ZrO₂ antireflection coating 88 having a thickness of $\lambda/4n_{\text{ZrO}_2}$. The structure layered as above is cleaved parallel to the paper surface, whereby the surface-emitting semiconductor element 89 is fabricated.

Note that it is desirable that the number of quantum wells in the multiple-quantum-well active layer 84 be 20 pairs or more in order to sufficiently absorb excitation light and

further preferable that it be about 24 pairs in order to prevent crack occurrence. The wavelength λ of light emitted by the surface-emitting semiconductor element 89 can be controlled in a range of 380 to 560 nm by the $\text{In}_{23}\text{Ga}_{1-23}\text{N}$ multiple-quantum-well active layer, and in the second embodiment, the wavelength λ is 520 nm for the green laser light source 1b and 450 nm for the blue laser light source 1c.

Next, the semiconductor laser unit, constructed of the aforementioned surface-emitting semiconductor element 89 and InGaN semiconductor laser element 74, will be described with reference to Fig. 8. As illustrated in Fig. 8A, the semiconductor laser unit includes an excitation light source 74'; the aforementioned surface-emitting semiconductor element 89 with the aforementioned distributed reflection film 87 bonded to a heat sink 106; a concave mirror 105 which is an output mirror; a laser resonator 109, constructed of the concave surface of the concave mirror 105 and the reflection mirrors 86 and 87 of the surface-emitting semiconductor element 89; and a Brewster plate 104, disposed within the laser resonator 109, for controlling polarization.

The excitation light 107 of wavelength 410 nm, emitted from the excitation light source 74' having an output of 4 W, is collected into the semiconductor layers of the surface-emitting semiconductor element 89 by a lens 102 and excites the surface-emitting semiconductor element 89. The light emitted from the excited surface-emitting semiconductor

element 89 resonates in the laser resonator 109, and laser light 108 emerges from the output mirror 105.

In the case of obtaining green laser light of wavelength 520 nm as the laser light 108, the output of the green laser light is 1 W. On the other hand, in the case of obtaining blue laser light of wavelength 450 nm as the laser light 108, the output is 2 W. The green or blue laser light 108, as in the first embodiment, is utilized for scanning the screen 9 two-dimensionally (see Fig. 1).

This case is also capable of eliminating the optical modulators 2b and 2c employed in the first embodiment, by directly modulating the semiconductor laser elements 74 of the excitation light source 74'. This accomplishes cost reduction.

Notice that as illustrated in Fig. 8B, the excitation light source 74' may be disposed at an angle to the surface-emitting semiconductor element 89 to suppress the light which returns the laser resonator 109 to the excitation light source 74'. In addition, the present invention is not limited to the surface-emitting semiconductor elements described above. For instance, the present invention is also able to employ surface-emitting semiconductor elements that have an active layer consisting of GaN, GaNAs, or InGaNAs. Furthermore, the present invention is not limited to the aforementioned semiconductor laser elements which serve as excitation light sources. For example, the present invention is able to employ other semiconductor laser elements which have an active layer

consisting of GaN, GaNAs, or InGaNAs.

Fig. 10 illustrates an excitation solid laser unit that can be employed in the color display of the present invention. This laser unit includes a semiconductor laser element 211 for emitting laser light (excitation light) 210, a collective lens 212 for collecting the emitted laser light 210, and a LiYF_4 crystal 213 which is a solid-state laser medium doped with Pr^{3+} (hereinafter referred to as a $\text{Pr}^{3+}:\text{LiYF}_4$ crystal).

The semiconductor laser element 211, the collective lens 212, and the $\text{Pr}^{3+}:\text{LiYF}_4$ crystal 213 are mounted on a Peltier element 214. In addition, a thermistor 215 for temperature detection is mounted on the Peltier element 214. An output signal from this thermistor 215 is input to a temperature control circuit (not shown). With this temperature control circuit, the Peltier element 214 is driven based on the output signal from the thermistor 214 so that the semiconductor laser element 211, the collective lens 212, and the $\text{Pr}^{3+}:\text{LiYF}_4$ crystal 213 are maintained at a predetermined temperature.

The semiconductor laser element 211 employs a broad area type InGaN semiconductor laser element having an oscillating wavelength of 440 nm. The $\text{Pr}^{3+}:\text{LiYF}_4$ crystal 213 is provided at its light incidence end face or rear end face 213a with a coating (with a reflectance of 99.9% or more) which permits satisfactory reflection of light of wavelength 479 nm, and is provided at its light emergence end face or front end face 213b with a coating which permits only only 1% transmission of light of wavelength

479 nm and reflection of the remaining light.

The laser light 210 with a wavelength of 440 nm, emitted from the InGaN semiconductor laser element 211, is incident on the rear end face 213a of the $\text{Pr}^{3+}:\text{LiF}_4$ crystal 213. The Pr^{3+} in the $\text{Pr}^{3+}:\text{LiF}_4$ crystal 213 is then excited with the incident laser light 210, and a transition of $^3\text{P}_0 \rightarrow ^3\text{H}_4$ causes light of wavelength 479 nm to occur. The light of wavelength 479 nm oscillates between the crystal end faces 213a and 213b provided with the aforementioned coatings and causes laser oscillation. The blue laser light 216 of wavelength 479 nm, generated in this manner, emerges from the front end face 213b of the crystal 213.

While the excitation solid laser unit for generating blue laser light has been described, the present invention is also capable of employing other excitation laser units for generating red laser light of wavelength 600 to 660 nm and green laser light of wavelength 515 to 555 nm by taking advantage of a transition of $^3\text{P}_0 \rightarrow ^3\text{F}_2$ or $^3\text{P}_0 \rightarrow ^3\text{H}_6$ and a transition of $^3\text{P}_1 \rightarrow ^3\text{H}_5$.

In addition, although the present invention has been described with reference to the preferred embodiments thereof, the invention is not to be limited to the details given herein, but may be modified within the scope of the invention hereinafter claimed.